

Cisco

300-610

Designing Cisco Data Center Infrastructure (DCID)



For More Information – Visit link below:

<https://www.examsboost.com/>

Product Version

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Latest Version: 15.1

Question: 1

What is an advantage of using OTV as compared to VPLS for data center redundancy?

- A. prevents loops on point-to-point links
- B. provides head-end replication
- C. uses a proactive MAC advertisement
- D. provides full-mesh connectivity

Answer: A

Explanation:

Reference: <https://community.cisco.com/t5/data-center-documents/understanding-overlay-transportvirtualization-otv/ta-p/3151502#toc-hid-1043251551>

Question: 2

DRAG DROP

A failure occurs on the network between two BFD and OSPF neighbors. Drag and drop the protocol actions from the left into the correct order on the right.

BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.

step 1

If an alternate path is available, routers immediately start converging on it.

Step 2

The BFD neighboring session with the OSPF peer is terminated.

Step 3

The local OSPF process tears down the OSPF neighbor relationship.

Step 4

Answer:

BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.

The BFD neighboring session with the OSPF peer is terminated.

If an alternate path is available, routers immediately start converging on it.

BFD notifies the local OSPF process that the BFD neighbor is no longer reachable.

The BFD neighboring session with the OSPF peer is terminated.

The local OSPF process tears down the OSPF neighbor relationship.

The local OSPF process tears down the OSPF neighbor relationship.

If an alternate path is available, routers immediately start converging on it.

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/ios/12_Os/feature/guide/fs_bfd.html#wp1238898

Question: 3

Which multicast rendezvous point redundancy mode is valid for Bidirectional PIM?

- A. Embedded RP
- B. Phantom RP
- C. MSDP
- D. PIM anycast RP

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/products/collateral/ios-nx-os-software/ipmulticast/whitepaper_c11-508498.html

Question: 4

An engineer deploys LISP VM mobility. Which feature is configured on the interfaces that have VM mobility enabled?

- A. IP redirects
- B. flow control
- C. proxy ARP
- D. HSRP

Answer: C

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/sw/nxos/lisp/configuration/guide/b_NX-OS_LISP_Configuration_Guide/b_NXOS_LISP_Configuration_Guide_chapter_010.html

Question: 5

What are two advantages of using Cisco vPC over traditional access layer designs? (Choose two.)

- A. supports Layer 3 port channels
- B. disables spanning-tree
- C. no spanning-tree blocked ports
- D. uses all available uplink bandwidth
- E. maintains single control plane

Answer: CD

Explanation:

Reference: https://www.cisco.com/c/dam/en/us/td/docs/switches/datacenter/sw/design/vpc_design/vpc_best_practices_design_guide.pdf

Thank You for Trying Our Product

For More Information – **Visit link below:**

<https://www.examsboost.com/>

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



Visit us at <https://www.examsboost.com/test/300-610/>