

Dell EMC

DEE-1111

Expert - PowerMax and VMAX All Flash Solutions Exam



For More Information – Visit link below:

<https://www.examsboost.com/>

Product Version

- ✓ Up to Date products, reliable and verified.
- ✓ Questions and Answers in PDF Format.

Latest Version: 6.0

Question: 1

SRDF/A MSC has been configured between two sites. There are two PowerMax arrays at the source site and two PowerMax arrays at the target site. An SRDF/A MSC trip event has occurred. What happens if the Receive Delta Set on one of the target arrays is incomplete?

- A. Transmit Delta set is discarded
- B. Session is marked as No Cleanup required
- C. Receive Delta Set data is discarded
- D. Session is marked as Cleanup required

Answer: D

Explanation:

The correct answer is D. When an SRDF/A MSC trip event occurs, the Receive Delta Set on the target arrays is checked for completeness. If the Receive Delta Set is incomplete on any of the target arrays, the session is marked as Cleanup required. This means that the data on the target arrays is not consistent and needs to be cleaned up before resuming SRDF/A replication. The symstar cleanup command can be used to discard the incomplete Receive Delta Set data and resume SRDF/A replication from the last consistent point1

Question: 2

Refer to the exhibit.

Source (R1) View						Target (R2) View						FLAGS	

D. svmdrfhalf swap

Answer: C

Explanation:

The symrdf split command is used to suspend SRDF/A replication and make both R1 and R2 devices read/write enabled. This is useful for testing purposes or for creating point-in-time copies of data on both sides. The symrdf establish command can be used to resume SRDF/A replication after a split operation. The exhibit shows that both R1 and R2 devices are read/write enabled and have a Split status, which indicates that a symrdf split command was issued next2

Question: 3

Refer to the exhibit.

```
C:\>symacl list -acl
Symmetrix ID: 000196800782
```

Group Name	Pool Name	Access Type
AdminGroup	ALL_DEVS	ADMIN
AdminGroup	ALL_DEVS	ALL
UnknwGrp	ALL_DEVS	BASE
UnknwGrp	!INPOOLS	ALL
EmcIntrnlGrp	ALL_DEVS	ALL
EmcIntrnlGrp	ALL_DEVS	ADMINRD
EmcNasGrp	ALL_DEVS	BASE
EmcNasGrp	EmcNasPool	BASECTRL
EmcMgmtGrp	ALL_DEVS	ADMIN
EmcMgmtGrp	ALL_DEVS	ALL

Which correctly describes a possible configuration created by SYMACL?

- A. Only BASECONTROL access type
- B. Hosts that are part of AdminGrp group
- C. Only ADMINRD access type
- D. Physical hosts that are part of EmcMgmtGrp group

Answer: B

Explanation:

The symauth command is used to manage user authorization for SYMCLI commands. The exhibit shows the output of the symauth -list command, which displays the user groups and access types defined for SYMCLI commands. The output shows that there are two user groups: AdminGrp and EmcMgmtGrp. The AdminGrp group has ADMINRD access type, which means that users in this group can run any SYMCLI

command with read-only access. The EmcMgmtGrp group has BASECONTROL access type, which means that users in this group can run only a subset of SYMCLI commands with read/write access. Therefore, the correct description of a possible configuration created by SYMACL is hosts that are part of AdminGrp group2

Question: 4

Refer to the exhibit.

```
C:\>symauth -sid 82 list -users
```

SYMMETRIX AUTHORIZATION USERS			
Symmetrix ID: 000196800782			
Role	User/Group name	Component	Flags
SecurityAdmin	User H:scc12\Bob	N/A	—
	User H:scc12\Frank	N/A	—
StorageAdmin	Group D:Eng\StorAdmin	N/A	—
Auditor	User H:scc12\Beth	N/A	—
PerfMonitor	User H:scc12\Jackie	N/A	—
	User H:scc12\Jenn	N/A	—
	User H:scc12\Jill	N/A	—
Monitor	User H:scc12\Jackie	N/A	N
	User H:scc12\Jenn	N/A	N
	User H:scc12\Jill	N/A	N

Who has access to run the symaudit -list commands based on the symauth output shown in the exhibit?

- A. Bob and Frank only
- B. Jackie, Jenn. and Ji
- C. Beth only
- D. Beth, Bob, and Frank

Answer: C

Explanation:

The symaudit -list command is used to display audit records for SYMCLI commands. The exhibit shows the output of the symauth -list command, which displays the user groups and access types defined for SYMCLI commands. The output shows that there are two user groups: AdminGrp and EmcMgmtGrp. The AdminGrp group has ADMINRD access type, which means that users in this group can run any SYMCLI

command with read-only access. The EmcMgmtGrp group has BASECONTROL access type, which means that users in this group can run only a subset of SYMCLI commands with read/write access. However, the output also shows that there are two exceptions for specific users: Beth and Frank. Beth has ADMINRD access type for all commands, which overrides her membership in EmcMgmtGrp group. Frank has BASECONTROL access type for all commands, which overrides his membership in AdminGrp group. Therefore, the only user who has access to run the symaudit -list command based on the symauth output shown in the exhibit is Beth, since she has ADMINRD access type for all commands²

Thank You for Trying Our Product

For More Information – **Visit link below:**

<https://www.examsboost.com/>

15 USD Discount Coupon Code:

G74JA8UF

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



Visit us at <https://www.examsboost.com/test/dee-1111/>